

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
30 May 2003 (30.05.2003)

PCT

(10) International Publication Number
WO 03/044530 A1

(51) International Patent Classification: **G01N 33/543**,
C12Q 1/68

(21) International Application Number: **PCT/DK02/00779**

(22) International Filing Date:
19 November 2002 (19.11.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
PA 2001 01724 19 November 2001 (19.11.2001) DK

(71) Applicant (for all designated States except US): **CAN-
TION A/S (DK/DK)**; Ørsted's Plads, Building 347,
DK-2800 Kgs. Lyngby (DK).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **FALTUM, Carsten**
[DK/DK]; Birkevej 1, DK-3489 Fredensborg (DK).

(74) Agent: **NKT Research & Innovation A/S SCION.DTU**;
Diplomvej. Bldg. 373, DK-2800 Kgs. Lyngby (DK).

(81) Designated States (national): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK (utility model), SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

WO 03/044530 A1

(54) Title: **SENSOR SYSTEM WITH A REFERENCE SURFACE MIMICKING THE DETECTION SURFACE BUT WITH LOW LIGAND BINDING CAPACITY**

(57) Abstract: The invention concerns a sensor system with at least two flexible units, a sensor unit and a reference unit. The sensor unit comprises a capture surface area functionalised by linking one or more functional groups comprising a capture ligand, such as a member of a specific binding pair. The reference unit comprises an imitated capture surface area which area has been functionalised by linking one or more functional groups, wherein said one or more functional groups linked to the imitated capture surface area of said reference unit do not include a ligand which is identical with said capture ligand. The capture ligand may e.g. be a specific binding partner for a biocomponent, preferably selected from the group consisting of RNA oligos, DNA oligos, PNA oligos, protein, peptides, hormones, blood components, antigen and antibodies. The sensor unit and the method make it possible to reduce the noise, because the signal obtained from the reference unit which is measuring the noise may be subtracted from a signal obtained from the sensor unit.

SENSOR SYSTEM WITH A REFERENCE SURFACE MIMICKING THE DETECTION SURFACE BUT WITH
LOW LIGAND BINDING CAPACITY

The present invention relates to a sensor system for
detecting the presence or the amount of a substance e.g.
5 a target biocomponent in a fluid such as a liquid.

Bagground of the invention

It is known from e.g. WO 0066266 and WO 9938007 that
10 micro-cantilevers can be used for detection of molecular
interaction. Capture molecules are immobilised on the
surface of the cantilever. When the capture molecules
bind to an analyte in the sample that is presented to the
cantilever, this will induce a change in the surface
15 stress of the cantilever, and consequently the cantilever
will deflect and/or stretch.

Measuring the reflection angle from a laser beam that is
directed to the cantilever can detect a deflection.
20 Another sensor principle is the use of a piezoresistor
integrated into the cantilever. In this detection
principle the deflection/stretch is detected as a change
in the electrical resistance of the piezoresistor.

25 The signal from the measuring cantilever comprises both
the signal from the deflection and stretch of the
cantilever but also from noise.

It has previously been demonstrated that a blank
30 cantilever can be coupled e.g. in a Wheatstones bridge
with the measuring cantilever in order to eliminate the
mechanical noise in the system which may include, but is
not limited to, external vibration, temperature changes
etc.

In this case the signal from the reference cantilever can be described as:

$$[2] \quad S_{\text{ref}} = S_{\text{mech. noise}}$$

5

where:

Sref = Total signal from the reference cantilever

The noise of the signal has thereby been reduced significantly. However, the signal measured still includes noise, and it is the object of the present invention to provide a sensor system where the amount of noise is even further reduced than in the prior art solutions described above.

15

Summary of the invention

It has been found that the signal from the measuring cantilever will be a combination of several components:

20

$$[1] \quad S_{\text{mc}} = S_{\text{spec. bind.}} + S_{\text{mech. noise}} + S_{\text{unspec. bind.}}$$

where:

S_{mc} = Total signal from the measuring cantilever

25 S_{spec. bind.} = Signal due to the specific binding of the analyte to capture molecules

S_{mech. noise} = Signal due to mechanical noise, e.g. external vibrations, temperature variation

30 S_{unspec. bind.} = Signal from unspecific binding of molecules in the sample to the capture molecules

Unspecific binding is a substantial problem in all binding assays as it is impossible today to distinguish between specific and unspecific binding. As can be seen 35 the formulas above and the use of a traditional reference cantilever do not eliminate this problem.

The objective of the invention is therefore to provide a sensor system which system does not have the drawbacks as described above. The invention as it is defined in the
5 claims provides a sensor system with a reduced level of noise compared to prior art sensors.

The sensor system according to the invention comprises at least two flexible units, wherein one of said units is
10 ``a sensor unit'' and another one is ``a reference unit''. The sensor unit comprises a capture surface area which area has been functionalised by linking one or more functional groups comprising a capture ligand to said capture surface area.

15 The reference unit comprises an imitated capture surface area, which area has been functionalised by linking, preferably covalently linking one or more functional groups. The reference unit differs from the sensor unit
20 in the composition of the functional groups linked to its surface. As it will be clear from the following, the main issue of the invention is that the reference unit is functionalised but that it contains less or no functional groups which are identical with the capture ligand of the
25 sensor unit. In one embodiment, the imitated surface area contains no or less members of the specific binding pair which is complementary to the same binding partner member as the capture ligand of the sensor unit.

Disclosure of the invention

The sensor system of the invention concerns a set-up as defined in the claims which system comprises a measuring
5 sensor unit which is coupled to an "intelligent" reference unit. In this set-up it has surprisingly turned out that the reference unit can be used to partly or totally eliminate not only mechanical noise, but also to reduce or eliminate the noise originating from unspecific
10 binding.

The sensor unit is functionalised by immobilising capture molecules as normally to a capture surface area of the sensor unit. Contrary to the normal procedure, the
15 reference unit is also functionalised at a surface area designated "an imitated capture surface area".

In one embodiment the noise is reduced significantly, e.g. to 50 % or lower compared to prior art technology.
20

In one embodiment, the noise resulting from unspecific binding is essentially eliminated i.e. within measuring uncertainty.

25 In the following the term "a ligand" means a type of ligand, and similarly "a binding partner" means a type of binding partner and so on.

Both the capture surface area (which means the capture
30 surface area of the sensor unit), and the imitated capture surface area (which means the imitated capture surface area of the reference unit) are functionalised by linking one or more functional groups to the surfaces, preferably so that the amount of proteins, amino acids
35 and/or lipids that binds via unspecific binding to the imitated capture surface area is closer to the amount of

similar components that binds via unspecific binding to the capture surface area than if the reference unit was not functionalised.

- 5 The functional groups linked to the capture surface area and the reference surface area, respectively, may be linked chemically e.g. covalently or ionic bondings; or physically. In one embodiment, one or more of the functional groups are linked via covalent bonds. In one
10 embodiment, one or more of the functional groups are linked by adsorption. Adsorption means a non-specific physical interaction between the functional groups and the surface area. Adsorption is relatively cheap, easily carried out, and tends to be less disruptive to enzymic
15 proteins than chemical means of attachment, the adsorption binding being mainly by hydrogen bonds, multiple salt linkages, and Van der Waal's forces. Adsorption bears the greatest similarity to the situation found in biological membranes in vivo and may therefore
20 in some embodiments be preferred.

The size of the sensor unit capture surface area and the size of the reference unit imitated surface area may differ from each other or it may be equal. If the size of
25 the sensor unit capture surface area and the size of the reference unit are equal to each other, the calculation of the signal with reduced or no noise is easier than if the sizes differ from each other. In the latter case, a correlation factor compensating for the size difference
30 should be implemented.

The capture ligand is a member of a specific binding pair. Such ligands which is members of a specific binding pair is well known in the art, and further, information
35 concerning such binding pair can be found in WO 0066266,

WO 9938007, US 5,156,810, WO 0036419 and WO 9631557 which publication are hereby incorporated by reference.

By the term specific bonding pair is meant any pair of
5 target molecule/capture ligand with an ability to
specifically bind to one another e.g. receptor/target
ligand, enzyme/substrate (or analogue), nucleic acid
binding protein/nucleic acid etc. Such specific bonding
pair of target molecule/capture ligand is thereby said to
10 be complementary to each other.

In one embodiment, the binding pair in the form of the
capture ligand binding partner and a target binding
partner is selected among antigen-antibodies or fragments
15 thereof and nucleic acid strands - nucleic acid strands.

In one embodiment, a molecule that shows similarity to
the capture molecules is immobilised to the reference
unit. The molecules on the reference unit though, in this
20 embodiment do not exhibit a specific binding to the
analyte that the assay is designed to detect.

In one embodiment, the one or more functional groups
linked to the imitated capture surface area of the
reference unit do not include a ligand, which is
25 identical with the capture ligand. In one embodiment, the
one or more functional groups linked to the surface area
of said reference unit do not include a ligand which is a
member of the specific binding pair.

30

The molecules on the reference unit can belong to any
class of molecules and do not necessarily have to be of
the same class as the molecules on the sensor unit.

35 In one embodiment, the functional group linked to the
imitated surface area of the reference unit includes a

reference ligand. The reference ligand may in one embodiment be present in a number which is 50 % or more such as 75 % or more, such as 90 % or more of the number of capture ligands on the capture surface of the sensor unit. In one embodiment, the reference ligand is of the same chemical class as the capture ligand of the sensor unit. The chemical class may e.g. be one of a) nucleic acids and strands thereof such as DNA oligos, PNA oligos, RNA oligos; b) proteins including peptides, antigen, antibodies and hormones; and c) lipids.

In one embodiment of the sensor system according to the invention, the sensor system is directed to detecting the presence of a preselected target biocomponent. The sensor unit comprises a capture surface area which area has been functionalised by linking a capture ligand, where said capture ligand is a capture ligand for the preselected target biocomponent. The reference unit comprises an imitated capture surface area which area has been functionalised by linking one or more functional groups, wherein the one or more functional groups of the imitated capture surface have less tendency to bind to the preselected target biocomponent than the capture ligand. In one embodiment, the functional groups linked to said imitated capture surface area of said reference unit do not include a ligand, which is a capture ligand for said preselected target biocomponent.

In one embodiment, the amount of proteins, amino acids and/or lipids that binds via unspecific binding to the imitated capture surface area is 50 % or more, such as 60 % or more, such as 70 % or more, such as 80 % or more, such as 90 % or more, such as essentially the same as the amount of similar components that binds via unspecific binding to the capture surface area. In one embodiment, this is measured by using DAKO Human Serum Protein

Calibrator as test medium. In one embodiment, this is measured by using DAKO Lipoprotein (a) Calibrator as test medium.

- 5 When a sample is presented to the sensor unit and reference unit, the analyte, which is a binding partner to the capture ligand (if present), will bind to the capture ligand on the sensor unit. Also various other molecules in the sample will unspecifically bind to the
10 functional groups on the sensor unit.

In one embodiment, it is desired that the one or more functional groups of the imitated capture surface have a capture tendency of 50 % or less, such as 40 % or less,
15 such as 30 % or less, such as 20 % or less, such as 10 % or less than the capture tendency of the capture ligand toward said preselected target biocomponent.

In one embodiment, the reference ligand of the reference
20 unit has essentially the same charge as the capture ligand of at least one sensor unit connected to the reference unit. Essentially the same charge means that the charge of the respective capture/reference ligands differs from each other by 10 % or less, preferably by 5
25 % or less measured in water.

In one embodiment, the imitated capture surface area of the reference unit has essentially the same pH value as the capture surface area of at least one sensor unit
30 connected to the reference unit. Essentially the same pH value means that the pH value of the respective surface areas differs from each other by 0.5 pH or less, preferably by 0.1 pH % or less measured in water.

In one embodiment, the reference ligand of the reference unit has essentially the same hydrophility as the capture ligand of the sensor unit.

- 5 In one embodiment, the reference ligand of the reference unit has essentially the same structure as the capture ligand except for the binding site or sites, which may e.g. be blocked, removed or replaced by non-active chemical group(s).

10

In one embodiment, the imitated capture surface area of the reference unit has a surface tension measured as contact angle to a water droplet which is the same $\pm 2^\circ$ as the surface tension of the capture surface area of the sensor unit.

15

- In one embodiment of the sensor system of the invention the capture ligand is present in a first concentration linked to the capture surface area, and the capture
20 ligand linked to the imitated capture surface area in a second concentration, wherein said second concentration is substantially less than the first concentration such as 50 % or less, such as 40 % or less, such as 30 % or less, such as 20 % or less, such as 10 % or less than the
25 first concentration. In this embodiment also a part of the signal originating from a bonding between capture ligand and target ligand will be suppressed, this effect may therefore further be used in determining concentrations of a target biocomponent in a sample.

30

- In one embodiment, it is desired that the sensor system according to the invention comprises one or more sensor units and one or more reference units, where at least one, preferably each of the sensor units, is connected to
35 at least one reference unit. The connection may preferably include a coupling of the connected sensor

unit and reference unit so that a signal obtained from the reference unit is subtracted from a signal obtained from the sensor unit, more preferably said sensor unit and said reference unit being coupled in a Wheatstones
5 bridge.

The sensor and the reference units are coupled in a way so that the signal from the reference unit (e.g. a cantilever) is subtracted from the signal from the sensor
10 unit (e.g. a cantilever). This could be done by coupling them in a Wheatstones bridge in the same way as described in WO 0066266 and disclosed in WO 0066266 FIG. 3, the figure and accompanying description hereby being incorporated by reference.

15 The sensor system according to the invention may in principle comprise an unlimited number of sensor units and reference units, and the invention includes embodiments wherein two or more sensor units are coupled
20 to one reference unit, and embodiments wherein two or more reference units are coupled to one sensor units. The sensor system may preferably include two or more sensor unit, preferably at least 5 sensor units, more preferably at least 10 sensor units, wherein each of said sensor
25 units preferably comprises a capture surface area which area has been functionalised by linking, preferably by adsorption linking one or more functional groups comprising a capture ligand to said capture surface area, the capture ligand linked to each sensor units being a
30 member of a specific binding pair. In one embodiment, the capture ligand on one sensor unit preferably is different from the capture ligand of another sensor unit. Thereby several specific target molecules may be detected by the sensor system simultaneously.

35

- In one embodiment, at least one sensor unit and at least one reference unit, which are preferably coupled, have substantially the same size. "Substantially the same size" means within a 10 % variation based on the largest of the sensor/reference units. In one embodiment, "substantially the same size" means within a 5 % variation based on the largest of the sensor/reference units.
- 10 In one embodiment of the system according to the invention, the sensor unit(s) and the reference unit(s), which are coupled together, and preferably all of the sensor units and the reference units may preferably have substantially identical shapes.
- 15 In one embodiment, at least one reference unit coupled to a sensor unit has a thickness which is identical $\pm 10\%$ of the thickness of the sensor unit.
- 20 In one embodiment, the capture surface area and imitated capture surface area of pair wise sensor/reference flexible units have substantially identical sizes, wherein "substantially identical" should mean within a difference of 20 %, preferably within a difference of 10 %, even more preferably within a difference of about 5 %.
- 25 The flexible unit may in principle have any shape. In one embodiment, the flexible unit or a part of the unit is sufficiently flexible to perform a measurable change due to a stress reaction on the capture surface area/imitated capture surface area when the analytes or substances to be detected are adsorbed or linked to the capture surface area. In one embodiment, the flexible unit should have a free flexing area which is not directly bonded to a solid material.
- 35

In one embodiment, the flexible units comprise one or more units selected from the group consisting of cantilevers, bridges and membranes. In one embodiment, the flexible units are of micro size, which means that
5 the flexible units have dimensions which are 500x500x500 μm or less, preferably 5x100x200 μm or less. The shape of the flexible units may e.g. be as described in US 6016686 WO 0066266.

10 In one embodiment, the flexible units comprise a piezoresistor by use of which it is possible to register change in stress of the capture surface area. Further information concerning this aspect can also be found in WO 0066266, which information is hereby incorporated by
15 reference.

The ligand linked to the sensor unit may preferably be linked via a spacer. Information concerning useful spacer molecules can be found in WO 9631557.

20 In one embodiment, the capture ligand is selected from the group consisting of RNA oligos, DNA oligos, PNA oligos, protein, peptides, hormones, blood components, antigen and antibodies.

25 In one embodiment, the capture ligand is a specific binding partner for a biocomponent, preferably selected from the group consisting of RNA oligos, DNA oligos, PNA oligos, protein, peptides, hormones, blood components,
30 antigen and antibodies.

The term biocomponent further includes biomolecules and biocomponents selected from the group consisting of tissue, cells, body fluids, blood components,
35 microorganism, derivatives thereof, or parts thereof.